

HD VoIP / IP-PBX / Conference COMPLETE SOLUTIONS



Nanthida : 081-431-8399

Paweena : 089-416-2256

**DATA IN
MOTION**

Tel : 0-2255-6691

info@datainmotion.co.th



GXP2130 v2

3 Line Enterprise HD IP Phone

Product Highlights

- 2.8" 320x240 pixel TFT color LCD display
- 3 line, 3 SIP accounts
- Dual Gigabit Ethernet ports 10/100/1000Mbps
- 4 programmable soft keys
- 4-way conferencing
- 8 dual-color BLF extension keys
- Integrated PoE (Power-over-Ethernet)
- Integrated real-time applications weather, currency, etc.
- Supports Bluetooth V2.1 and EHS
- Automated provisioning
- HD audio

GXP2140

4-line Enterprise HD IP Phone

Product Highlights

- 4.3" 480x272 pixel TFT color LCD display
- 4 line, 4 SIP accounts
- Dual Gigabit Ethernet ports 10/100/1000Mbps
- 5 programmable soft keys
- 5-way conferencing
- 4 cascaded extension modules with LCD display
- Integrated PoE (Power-over-Ethernet)
- Integrated applications weather, currency, etc.
- Supports Bluetooth V2.1, USB, and EHS
- Automated provisioning
- HD audio

GXP2160

6-line Enterprise HD IP Phone

Product Highlights

- 4.3" 480x272 pixel TFT color LCD display
- 6 line, 6 SIP accounts
- Dual Gigabit Ethernet ports 10/100/1000Mbps
- 5 programmable soft keys
- 5-way conferencing
- 24 dual-color BLF extension keys
- Integrated PoE (Power-over-Ethernet)
- Integrated applications weather, currency, etc.
- Supports Bluetooth V2.1, USB, and EHS
- Automated provisioning
- HD audio

GVC3200

Full HD Video Conferencing System

Product Highlights

- Runs Android 4.4 and offers video conferencing apps in the Google Play Store
- Embedded MCU supports up to 4-way (1080p), 5-way (720p), 9-way (VGA) video conferencing
- Cross-protocol conference between SIP and any Android video conferencing apps
- 3x HDMI output, 1x VGA/HDMI input
- Dual-band Wi-Fi, Bluetooth 4.0, Gigabit network port, SD interface
- Bluetooth-based multi-touch remote control
- Remote-controllable wide-angle PTZ camera with 12x optical zoom
- State-of-the-art H.264 High Profile video compression and FEC technology
- FPGA based hardware implementation of advanced ISP technology
- Interoperable with 3rd party SIP-based video conferencing solutions using BFCP

HandyTone ATA/AD



UCM6100 Series



Product Highlights

- 1GHz ARM Cortex A8 application processor (multi-core DSP)
- Large memory (512MB DDR RAM, 4GB NAND Flash)
- Integrated 2/4/8/16 FXO ports (PSTN trunk)
- Integrated 2 FXS ports (Analog telephone) with lifeline
- Integrated 50 SIP trunk accounts
- Single Gigabit network ports 10/100/1000Mbps (UCM6108/6116)
- Dual Gigabit network ports 10/100/1000Mbps (UCM6104)
- Integrated PoE, USB, SD card
- Hardware DSP based 128ms-tail-length carrier-grade (LEC)
- Supports up to 500 SIP endpoints registrations
- 60 concurrent calls, 32 conference attendees

HandyTone 702/704

Analog Telephone Adaptor

Product Highlights

- 2 FXS ports (HT702) or 4 FXS ports (HT704)
- Supporting 3 REN
- Single 10/100Mbps Ethernet port (RJ45)
- 3-way conference
- Caller ID, call waiting, transfer, forward, etc.
- Voice codecs: G.711 with Annex I/J, G.723.1, G.729A/B, G.726, iLBC
- T.38 fax
- Secure & automated provisioning (TR069 & HTTP/HTTPS/TFTP)